

DriPak® 25

Description

Made of synthetic, water resistance media featuring a unique, configuration. Ideal for use in healthcare facilities, automotive paint booth, commercial buildings and a variety of industrial applications. Available with INTERSEPT® antimicrobial.

Application

Available for all ranges of applications in the AHU. For industry such as: Semiconductor, Automotive, Pharmaceutical, Commercial & Industrial, Gas turbine.



Specifications

| DriPak® 25 | |
|---------------------|-------------------------|
| Media | Synthetic pocket |
| Frame | Galvanised Steel Header |
| Efficiencies | G4 |
| Nominal depth | 305, 600 |
| Max. Operating Temp | 66°C |
| Final Resistance | 375 Pa |
| Test Certification | UL Certified |

Product Features & Benefits

- Patented pocket design
- Sturdy construction
- Synthetic media maximizes filtration

| No | Size (mm) | Pocket Length (mm) | Pocket | Air Flow m³/hr | IR (Pa) G3 |
|----|-----------|--------------------|--------|----------------|------------|
| 1 | 594x594 | 305 | 8 | 3400 | 55 |
| 2 | 289x594 | 305 | 4 | 1700 | 55 |
| 3 | 594x594 | 600 | 6 | 3400 | 45 |
| 4 | 289x594 | 600 | 3 | 1700 | 45 |

